



PC Module MT63A

A Unique Interchangeable
120-pin PC module
built for Superior performance.

Upgrade your tutortouch panel experience with our pluggable desktop PC module.

Collaboration, Design and Presentation delivery made easy with our enhanced i5 or i7 modules.



PRODUCT SPECIFICATIONS

Feature's
I/O Port
Power
Physical Specifications
Environmental Conditions

PC Module MT63A

PRODUCT SPECIFICATIONS



| SPECIFICATION | |
|----------------------------|--|
| Type | Detachable PC Module |
| CPU | Intel 10th Generation CPU / Intel® Core™ i5 10500 (3.8GHz) Intel 10th Generation CPU / Intel® Core™ i7 10700 (4.5GHz) |
| Memory | DDR4 4 GB / 8 GB / 16 GB optional |
| Optional Hard disc | SSD: 256GB NMVE / 512GB optional |
| Chip set | Intel H410 |
| Graphics | Intel® UHD Graphics 630 |
| Sound Card | Integreted High Definition Audio Stereo |
| Network | 1000M |
| Wi-fi | 802.11 ac (2.4 Ghz / 5 GHz) |
| Bluetooth | 4.2 |
| Operating System | Windows 10 (Microsoft license for the pre-installed OS is supposed to be obtained by the customers themselves.) |
| POWER | |
| Power Supply Mode | Internal Power Supply Mode |
| Power Requirements | 100-240 V ~ 50 / 60Hz 1.5A |
| Max Power | 75 W |
| Standby Power | 5 W |
| PHYSICAL SPECIFICATION | |
| Dimension L*W* H | 263.4 x 246.1 x 32.2 m |
| Dimension (Package) L*W* H | 1 pcs (353 x 312 x 91 mm) / 5pcs (495 x 367 x 337 mm) |
| Net Weight | 1.81 kg |
| Gross Weight | 1 pcs (2.36 kg) / 5pcs (13.56 kg) |

PC Module MT63A

PRODUCT SPECIFICATIONS



| I/O PORT | |
|-------------------------|--|
| Antenna | 2 |
| USB 2.0 | 2 |
| USB 3.0 | 4 |
| USB 3.0 Gen 1 Type-C | 1 |
| DP UOT | 1 |
| HDMI Out. | 1 |
| MIC IN | 1 |
| LINE OUT | 1 |
| RJ45 | 1 |
| HDD_LED | 1 |
| POWER_LED | 1 |
| 120 PIN | Support |
| ENVIRONMENTAL CONDITION | |
| Operation Temperature | 0°C - 45°C |
| Operation Humidity | 10 % - 90 % RH |
| Storage Temperature | -20°C - 60°C |
| Storage Humidity | 10 % - 90 % RH |
| ESD | |
| Contact Discharge | 34 KV passed level A test / 36 KV passed level B test |
| Non-contact Discharge | 38 KV passed level A test / 312 KV passed level B test |

visit our website
for more

