



PC Module OPS42

**Simplicity meets
Excellent Performance.**

Designed to be easy to use, giving you business-class performance, enhanced security features and remote manageability to reduce cost.



PRODUCT SPECIFICATIONS

- Feature's
- I/O Port
- Power
- Physical Specifications
- Environmental Conditions

PC Module OPS42

PRODUCT SPECIFICATIONS



| SPECIFICATION | |
|----------------------------|--|
| Type | Detachable PC Module |
| CPU | Intel 8th Generation CPU / Intel® Core™ i3 8145U (2.1GHz), Intel 8th Generation CPU / Intel® Core™ i5 8265U (1.6GHz), Intel 8th Generation CPU / Intel® Core™ i7 8565U (1.8GHz) optional |
| Memory | DDR4 4 GB / 8 GB / 16 GB optional |
| Optional Hard disc | HDD (SATA 500GB / 1TB Optional) / SSD (M.2 128GB / 256GB / 512GB optional) |
| Chip set | Intel H310 |
| Graphics | Intel® UHD Graphics 620 |
| Sound Card | Integrated High Definition Audio Stereo |
| Network | 1000M |
| Bluetooth | 4.2 |
| Operating System | (Microsoft licence for the pre-installed OS is supposed to be optioned by the costumers themselves.) |
| POWER | |
| Power Supply Mode | Internal Power Supply Mode |
| Power Requirements | 12 - 19 V DC 5.0 A |
| Max Power | 90 W |
| Standby Power | 1.2 W |
| PHYSICAL SPECIFICATION | |
| Dimension L*W* H | 202.4 x 135,5 x 30 mm |
| Dimension (Package) L*W* H | 1 pcs (267 x 192 x 72 mm) / 10 pcs (551 x 378 x 220 mm) |
| Net Weight | 0.74 kg |
| Gross Weight | 1 pcs 1.74 kg / 10 pcs 18.4 kg |

PC Module OPS42

PRODUCT SPECIFICATIONS



| I/O PORT | |
|-------------------------|--|
| USB 2.0 | 2 |
| USB 3.0 | 2 |
| USB 3.0 Gen 1 Type-C | 1 |
| HDMI OUT | 1 |
| MIC IN | 1 |
| AUDIO OUT | 1 |
| RJ45 | 1 |
| 80 PIN | Support |
| OTHER FUNCTIONS | |
| HDD_LED | 1 |
| POWER_LED | 1 |
| Antenna | 2 |
| Kensington Lock | 1 |
| System Recovery Button | 1 |
| Power Button | 1 |
| ENVIRONMENTAL CONDITION | |
| Operation Temperature | 0°C - 45°C |
| Operation Humidity | 10% - 90%RH |
| Storage Temperature | -20°C -60°C |
| Storage Humidity | 10% - 90%RH |
| ESD | |
| Contact Discharge | ±4 KV passed level A test / ±6 KV passed level B test |
| Non-contact Discharge | ±8 KV passed level A test / ±12 KV passed level B test |

visit our website
for more

